

Category:How to

From "AllStarLink Wiki"

This is the list of all of the How To's.

Subcategories

This category has only the following subcategory.

U

- URI

Pages in category "How to"

The following 53 pages are in this category, out of 53 total.

A

- Activity Timer
- Add or Change DTMF Functions
- Adjusting USB Radio Audio Levels
- AllStar Link Registration
- AllStar Link Standard Commands
- ASL DEBIAN-9 INSTALL ON VULTR
- Audio Filters

B

- Backup
- Blacklist or whitelist
- Broadcastify

C

- Calibrating Audio Levels
- Call Sign Changes
- Change Callsign
- Coding standards
- Courtesy Tones
- Custom Repeater Splits

D

- DAHDI Make

E

- Editing Config Files

- Elke Link
- European Repeater Operation
- Event Management

F

- Fix Zaptel After a Yum Update

G

- Getting Started Overview

H

- How to Move a Node from one machine to another

L

- Linux Screen command

M

- Manipulating GPIO

N

- Node Registration
- Node Statistics

P

- Parrot mode
- Permanent Node Connection

R

- Radio Connections
- Recording Audio Files
- Remote Base
- RTCM Channel Driver
- RTCM Client
- RTCM Firmware upgrading
- RX Toneburst

S

- Setup Autopatch
- Setup IAXRPT use
- Simple voter
- Sleep Mode
- Standard Node vs Remote Base
- Starting and Stopping Asterisk

T

- Telemetry
- TheLinkBox
- Transmitting Tone Sequences
- Two Nodes on One Server
- Two Servers Behind NAT Router

U

- Update from SVN

W


- Web Transceiver
- WebTransceiver on MAC
- Whats Required
- WiKi Getting Started

Media in category "How to"

The following 2 files are in this category, out of 2 total.



ASL two servers one ...
57 KB



Two ASL servers one...
35 KB

Retrieved from "http://wiki.allstarlink.org/w/index.php?title=Category:How_to&oldid=104"

-
- This page was last modified on 9 October 2017, at 15:49.